



# WRANGLER MT/R<sup>®</sup> WITH KEVLAR<sup>®</sup>

THE REVOLUTIONARY OFF-ROAD TIRE BUILT WITH THE RUGGED TOUGHNESS OF DUPONT™ KEVLAR<sup>®</sup> FOR ENHANCED SIDEWALL PUNCTURE RESISTANCE

The Wrangler MT/R<sup>®</sup> with Kevlar<sup>®</sup> is Goodyear's first off-road tire to incorporate DuPont Kevlar<sup>®</sup>, an innovative material that's, pound for pound, five times stronger than steel. The innovative use of Kevlar<sup>®</sup> brings superb sidewall cut and puncture resistance to an area of the tire that demands extra toughness when driving off-road. It also helps reinforce the sidewall for when you return to the pavement.

## Wrangler MT/R with Kevlar<sup>®</sup> Features/Benefits

-  **DUPONT KEVLAR<sup>®</sup> REINFORCED SIDEWALLS** help increase sidewall puncture resistance by 35% for confidence in tough terrain\*
-  **HARDWORKING WRAPAROUND TREAD** offers enhanced sidewall traction in deep mud, sand and rocks
-  **INNOVATIVE ASYMMETRIC TREAD DESIGN** offers aggressive off-road traction while maintaining enhanced handling on the road
-  **ADVANCED SILICA RUBBER** for superb off-road and wet traction

\*Source: Goodyear Sidewall Penetration Energy – LT285/70R17 LR-D – 65 psi  
DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company used under license by The Goodyear Tire & Rubber Company and affiliates.

**GOODYEAR**  
MORE DRIVEN.



# WRANGLER MT/R<sup>®</sup> WITH KEVLAR<sup>®</sup>

## THE RIGHT SIZE FOR THE JOB

The Wrangler MT/R<sup>®</sup> with Kevlar<sup>®</sup> is available in a wide selection of sizes to fit popular trucks and for big plus-size off-road applications. To find your size or to learn more about the revolutionary Wrangler MT/R with Kevlar<sup>®</sup>, stop by the Goodyear<sup>®</sup> Retailer in your neighborhood or visit [www.goodyear.com](http://www.goodyear.com).

## SPECIFICATIONS

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	TREAD DEPTH (32NDS)	REVS/MILE
31X10.50R15LT	1090	C	BSL	750710326	219336	7.0 - 9.0	8.5	10.6	30.8	2,270	19	681
32X11.50R15LT	1130	C	BSL	750732326	219346	8.0 - 10.0	9.0	11.4	31.8	2,535	21	655
33X12.50R15LT	1080	C	BSL	750711326	219335	8.5 - 11.0	10.0	12.5	32.8	2,205	21	635
35X12.50R15LT	1130	C	BSL	750712326	208009	8.5 - 11.0	10.0	12.5	34.8	2,535	21	598
LT235/85R16	1200	E	BSL	750713326	208010	6.0 - 7.5	6.5	9.3	31.7	3,042	18	659
LT245/75R16	1200	E	BSL	750151326	219334	6.5 - 8.0	7.0	9.8	30.7	3,042	18	686
LT265/75R16	1230	E	BSL	750153326	219332	7.0 - 8.0	7.5	10.5	31.7	3,415	18	660
LT285/75R16	1260	E	BSL	750451326	219333	7.5 - 9.0	8.0	11.3	33.1	3,750	18	637
LT305/70R16	1240	E	BSL	750475326	219344	8.0 - 9.5	9.0	12.2	33.1	3,525	18	637
LT315/75R16	1210	D	BSL	750554326	207999	8.0 - 10.0	8.5	12.3	34.8	3,195	21	598
*33X10.50R17LT	1180	E	BSL	750185755	234947	7.0 - 9.0	8.5	10.54	32.52	2,910	21	635
35X12.50R17LT	1110	C	BSL	750740326	208003	8.5 - 11.0	10.0	12.5	34.8	2,405	21	598
37X12.50R17LT	1240	D	BSL	750578326	208000	8.5 - 11.0	10.0	12.5	36.8	3,525	21	566
38X14.50R17LT	1210	D	BSL	750736326	208013	10.0 - 12.0	12.0	14.7	37.8	3,195	21	551
40X13.50R17LT	1210	C	BSL	750623326	216483	8.5 - 11.0	11.0	13.6	39.8	3,195	22	523
40X13.50R17LT	1210	C	BSL	750622326	208001	8.5 - 11.0	11.0	13.6	39.8	3,195	21	523
42X14.50R17LT	1210	C	BSL	750624326	216485	10.0 - 12.0	12.0	14.7	41.8	3,195	22	497
42X14.50R17LT	1210	C	BSL	750625326	208002	10.0 - 12.0	12.0	14.7	41.8	3,195	21	498
LT245/70R17	1190	E	BSL	750140326	219342	6.5 - 8.0	7.0	9.8	30.6	3,000	18	684
LT245/75R17	1210	E	BSL	750707326	219339	6.5 - 7.5	7.0	9.8	31.7	3,195	18	663
LT255/75R17	1110	C	BSL	750687326	208560	6.5 - 8.5	7.0	10.0	32.3	2,405	19	644
LT265/70R17	1210	E	BSL	750152326	219331	7.0 - 8.5	8.0	10.7	31.7	3,195	18	660
LT275/70R17	1210	E	BSL	750393326	219349	7.0 - 8.5	8.0	11.0	32.4	3,195	18	649
*275/80R17	1210	D	BSL	750190755	234948	7.5 - 9.0	8.0	10.98	34.32	3,195	21	609
LT285/70R17	1210	D	BSL	750434326	219280	7.5 - 9.0	8.5	11.5	33.0	3,195	19	638
LT305/70R17	1190	D	BSL	750542326	219337	8.0 - 9.5	9.0	12.2	34.1	3,000	19	617
LT315/70R17	1210	D	BSL	750551326	219340	8.5 - 10.0	9.5	12.7	34.7	3,195	21	607
*33X10.50R18LT	1160	D	BSL	750186755	234949	7.5 - 9.5	8.5	10.54	32.52	2,755	21	635
35X12.50R18LT	1230	E	BSL	750032326	216875	8.5 - 11.0	10.0	12.5	34.8	3,415	18	598
*37X13.50R18LT	1240	D	BSL	750189755	234981	8.5 - 11.0	11.0	13.58	36.52	3,525	21	566
LT275/65R18	1130	C	BSL	750392326	219348	7.5 - 9.0	8.0	11.0	32.1	2,535	19	651
LT275/70R18	1250	E	BSL	750432326	219338	7.0 - 8.5	8.0	11.0	33.4	3,640	18	630
LT285/75R18	129P	E	BSL	750116326	226371	7.5 - 9.5	8.0	11.3	35.1	4,080	18	593
*LT295/70R18	1290	E	BSL	750188755	234950	7.5 - 10.0	8.5	11.77	34.29	4,080	18	610
33X12.50R20LT	1140	E	BSL	750035326	216879	8.5 - 11.0	10.0	12.5	32.8	2,600	18	633
35X12.50R20LT	1210	E	BSL	750002326	216874	8.5 - 11.0	10.0	12.5	34.8	3,195	18	598
*37X12.50R20LT	1260	E	BSL	750191755	234982	8.5 - 11.0	10.0	12.50	36.52	3,750	18	566
LT275/65R20	1260	E	BSL	750714326	208011	7.5 - 9.5	8.0	11.0	34.1	3,750	18	610
LT285/65R20	1270	E	BSL	750435326	207993	8.0 - 10.0	8.5	11.5	34.8	3,860	18	598

\*Launching in 4th Quarter, 2018

## POPULAR VEHICLE FITMENTS

- Chevy 1/2-ton, 3/4-ton, 1-ton trucks
- Dodge 1/2-ton, 3/4-ton, 1-ton trucks
- Ford 1/2-ton, 3/4-ton, 1-ton trucks
- GMC 1/2-ton, 3/4-ton, 1-ton trucks
- Hummer H2, H3
- Jeep Grand Cherokee
- Jeep Wrangler
- Nissan Xterra
- Toyota FJ Cruiser
- Toyota Tundra



For more complete information, go to Tire-HQ™ at [www.tire-hq.com](http://www.tire-hq.com).

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company used under license by The Goodyear Tire & Rubber Company and affiliates.

©2018 The Goodyear Tire & Rubber Company. All rights reserved.

70050156197700 052707 - 01/18

**GOODYEAR**  
MORE DRIVEN.