

MARKET LEADER†



#1 PASSENGER REPLACEMENT TIRES†

#1 ORIGINAL EQUIPMENT CONSUMER TIRES†

# ASSURANCE® ALL-SEASON

## CRUISE THE ROAD

### ■ STEADFAST RIDE

Enjoy feeling connected to the road with biting edges that provide plenty of traction, plus improved stability

### ■ MAINTAIN TRACTION

Take on rainy conditions thanks to grooves that expel water quickly to keep you on the road

### ■ PLEASANTLY EFFICIENT

Appreciate peace and quiet; without sacrificing fuel economy with an optimized tread pattern

### ■ SMOOTH OPERATION

Experience a steady ride and confident handling on the road ahead, compliments of large stable shoulder blocks



105,000 Kilometre  
Tread Life Limited Warranty

\*See warranty brochure for complete details.



† Source Modern Tire Dealer (2020 Facts Issue), 2020 Facts Section: 2019 US Replacement Tires (see page 32); 2019 OE Consumer Tires (see page 33).

# ASSURANCE® ALL-SEASON AVAILABLE SIZES

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	REVS/ MILE	TREAD DEPTH (IN 32NDS)	UTQG
185/65R14	86 T	SL	VS	407106374	224948	5.0-6.5	5.5	7.4	23.5	1,168	889	9	600 A B
185/70R14	88 T	SL	VS	407476374	226972	4.5-6.0	5.5	7.4	24.3	1,235	860	9	600 A B
195/70R14	91 T	SL	VS	407736374	224957	5.0-6.5	6	7.9	24.8	1,356	843	9	600 A B
175/65R15	84 H	SL	VS	407955374	236543	5.0-6.0	5	6.97	23.98	1,102	872	9	600 A B
185/60R15	84 T	SL	VS	407739374	224956	5.0-6.5	5.5	7.5	23.8	1,102	878	9	600 A B
185/65R15	88 T	SL	VS	407259374	224943	5.0-6.5	5.5	7.4	24.5	1,235	853	9	600 A B
195/60R15	88 T	SL	VS	407740374	224937	5.5-7	6	7.9	24.2	1,235	864	9	600 A B
195/65R15	91 T	SL	VS	407477374	224932	5.5-7.0	6	7.9	25	1,356	836	9	600 A B
205/60R15	91 T	SL	VS	407741374	224949	5.5-7.5	6.5	8.2	24.7	1,356	846	9	600 A B
205/65R15	94 T	SL	VS	407478374	224946	5.5-7.5	6	8.3	25.5	1,477	820	9	600 A B
205/70R15	96 T	SL	VS	407785374	224952	5.0-7.0	6	8.2	26.3	1,565	795	9	600 A B
205/75R15	97 T	SL	VS	407789374	226975	5.0-7.0	5.5	8	27.1	1,609	771	9	600 A B
215/65R15	96 T	SL	VS	407791374	226978	6-7.5	6.5	8.7	26	1,565	804	9	600 A B
215/70R15	98 T	SL	VS	407783374	224945	5.5-7.0	6.5	8.7	26.9	1,653	777	9	600 A B
215/75R15	100 T	SL	VS	407792374	226980	5.5-7.0	6	8.5	27.7	1,764	756	9	600 A B
185/55R16	83 H	SL	VS	407001374	236544	5.0-6.5	6	7.64	24.02	1,074	870	9	600 A B
195/50R16	84 V	SL	VS	407002374	236545	5.5-7.0	6	7.91	23.7	1,102	882	9	600 A B
195/55R16	87 T	SL	VS	407787374	224955	5.5-7.0	6	7.9	24.4	1,201	857	9	600 A B
205/50R16	87 H	SL	VS	407788374	226973	5.5-7.5	6.5	8.4	24.1	1,201	867	9	600 A B
205/55R16	91 H	SL	BS	407781374	224930	5.5-7.5	6.5	8.4	24.9	1,356	839	9	600 A B
205/60R16	92 T	SL	VS	407212374	224939	5.5-7.5	6	8.2	25.7	1,389	813	9	600 A B
205/65R16	95 H	SL	VS	407780374	226974	5.5-7.5	6	8.2	26.5	1,521	789	9	600 A B
215/55R16	93 H	SL	VS	407525374	226977	6-7.5	7	8.9	25.3	1,433	827	9	600 A B
215/60R16	95 T	SL	VS	407562374	224931	6.0-7.5	6.5	8.7	26.1	1,521	801	9	600 A B
215/65R16	98 T	SL	VS	407016374	224947	6.0-7.5	6.5	8.7	27	1,653	774	9	600 A B
215/70R16	100 T	SL	VS	407782374	224938	5.5-7	6.5	8.7	27.9	1,764	749	9	600 A B
225/55R16	95 H	SL	VS	407165374	226991	6.0-8.0	7	9.2	25.8	1,521	810	9	600 A B
225/60R16	98 T	SL	VS	407715374	224936	6.0-8.0	6.5	9	26.6	1,653	786	9	600 A B
225/65R16	100 T	SL	VS	407786374	224953	6.0-8.0	6.5	9	27.5	1,764	760	9	600 A B
235/60R16	100 T	SL	VS	407784374	224951	6.5-8.5	7	9.5	27.1	1,764	771	9	600 A B
235/65R16	103 T	SL	VS	407207374	224944	6.5-8.5	7	9.5	28	1,929	746	9	600 A B
235/70R16	106 T	SL	VS	407866374	232861	6.0-8.0	7	9.45	28.98	2,094	721	9	600 A B
205/50R17	89 V	SL	VS	407582374	234167	5.5-7.5	6.5	8.43	25.12	1,279	832	9	600 A B
215/45R17	87 V	SL	VS	407568374	236547	7.0-8.0	7	8.39	24.65	1,201	848	9	600 A B
215/50R17	91 V	SL	VS	407790374	226976	6-7.5	7	8.9	25.5	1,356	820	9	600 A B
215/55R17	94 H	SL	VS	407213374	224933	6.0-7.5	7	8.9	26.3	1,477	795	9	600 A B
215/60R17	96 T	SL	VS	407348374	224954	6.0-7.5	6.5	8.7	27.2	1,565	768	9	600 A B
215/65R17	99 T	SL	VS	407719374	226979	6-7.5	6.5	8.7	28	1,709	746	9	600 A B
225/45R17	91 V	SL	VS	407003374	236546	7.0-8.5	7.5	8.86	24.96	1,356	837	9	600 A B
225/50R17	94 V	SL	VS	407372374	229734	6.0-8.0	7	9.17	25.91	1,477	807	9	600 A B
225/55R17	97 T	SL	VS	407726374	224941	6.0-8.0	7	9.2	26.8	1,609	780	9	600 A B
225/60R17	99 T	SL	VS	407723374	224940	6.0-8.0	6.5	9	27.6	1,709	757	9	600 A B
225/65R17	102 T	SL	VS	407285374	224934	6.0-8.0	6.5	9	28.5	1,874	733	9	600 A B
235/55R17	99 T	SL	VS	407599374	226994	6.5-8.5	7.5	9.7	27.2	1,709	768	9	600 A B
235/65R17	104 T	SL	VS	407722374	224942	6.5-8.5	7	9.5	29.1	1,984	718	9	600 A B
235/60R17	102 T	SL	VS	407323374	224950	6.5-8.5	7	9.5	28.1	1,874	744	9	600 A B
225/45R18	91 V	SL	VS	407938374	236631	7.0-8.5	7.5	8.86	25.94	1,356	806	9	600 A B
225/55R18	98 H	SL	VS	407867374	232863	6.0-8.0	7	9.17	27.76	1,653	753	9	600 A B
225/60R18	100 H	SL	VS	407795374	226992	6.0-8.0	6.5	9	28.6	1,764	731	9	600 A B
235/45R18	94 V	SL	VS	407991374	236634	7.5-9.0	8	9.29	26.34	1,477	793	9	600 A B
235/50R18	97 H	SL	VS	407004374	236550	6.5-8.5	7.5	9.65	27.28	1,609	766	10	600 A B
235/55R18	100 H	SL	VS	407826374	232862	6.5-8.5	7.5	9.65	28.15	1,764	742	9	600 A B
235/60R18	103 H	SL	VS	407815374	236549	6.5-8.5	7	9.45	29.09	1,929	718	9	600 A B
235/65R18	106 H	SL	VS	407885374	236632	6.5-8.5	7	9.45	30.04	2,094	696	9	600 A B
245/45R18	96 V	SL	VS	407005374	236633	7.5-9.0	8	9.57	26.65	1,565	784	10	600 A B
245/60R18	105 H	SL	VS	407819374	236639	7.0-8.5	7	9.76	29.57	2,039	707	10	600 A B
225/55R19	99 V	SL	VS	407930374	236635	6.0-8.0	7	9.17	28.78	1,709	726	9	600 A B
235/55R19	101 H	SL	VS	407924374	234168	6.5-8.5	7.5	9.65	29.17	1,819	716	9	600 A B
245/55R19	103 V	SL	VS	407971374	236638	7.0-8.5	7.5	9.96	29.65	1,929	705	10	600 A B
245/50R20	102 H	SL	VS	407870374	236636	7.0-8.5	7.5	9.96	29.69	1,874	704	9	600 A B
255/50R20	105 H	SL	VS	407006374	236637	7.0-9.0	8	10.43	30.08	2,039	695	9	600 A B

PLUS-SIZING DISCLAIMER WARNING: Before you replace tires, always consult the vehicle owner's manual and follow the vehicle manufacturer's replacement tire recommendations. Vehicle handling may be significantly affected by a change in tire size or type. When selecting tires that are different from the Original Equipment size, see a professional installer in order to make certain that proper clearance, load-carrying capacity and inflation pressure are selected. Never exceed the maximum load capacity and inflation pressure listed on the sidewall of the tire. Always drive safely and obey all traffic laws. Avoid sudden, sharp turns or lane changes. Failure to follow this warning may result in loss of control of the vehicle, leading to an accident and serious injury or death.

For more complete information, go to Tire-HQ™ at [www.tire-hq.com](http://www.tire-hq.com).  
©2020 The Goodyear Tire & Rubber Company. All rights reserved.



Scan code for product video

