

KELLY TIRES™



EDGE AT®

A Hardworking, Quality Tire with All-Terrain Traction for Everyday Driving

- **Flared tread block edges** help shovel mud, dirt and gravel off the tread for off-road traction
- **Deep tread grooves** evacuate water and slush from the tread for an enhanced on-highway grip
- **Sturdy tread blocks** stabilize the tread footprint to promote long treadwear
- **Proven tread pattern** enhances wet traction on the highway and improves endurance for off-road terrain

50000
MILE TREAD LIFE
LIMITED WARRANTY*

80,000 Kilometres

KELLY  TIRES™

30day
test

*See 30-Day Test Drive brochure for complete details.



EDGE AT® AVAILABLE SIZES

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	TREAD DEPTH (IN 32 ^{nds})	REVS/ MILE
225/75R15	102S	SL	OWL	357757286	228659	6.0 - 7.5	6	8.8	28.3	1,874	12	738
235/75R15	105S	SL	OWL	357571286	221753	6.8 - 8.0	6.5	9.3	28.9	2,039	12	724
225/75R16	104S	SL	OWL	357748286	225788	6.0 - 7.5	6	8.8	29.3	1,984	12	714
235/70R16	106T	SL	OWL	357206286	228215	6.8 - 8.0	7	9.5	29	2,094	12	721
235/75R16	112S	XL	OWL	357760286	228668	6.0 - 8.0	6.5	9.3	29.8	2,469	12	700
245/70R16	107T	SL	OWL	357762286	226571	6.5 - 8.0	7	9.8	29.5	2,149	12	707
245/75R16	111S	SL	OWL	357566286	225770	6.5 - 8.0	7	9.8	30.5	2,403	12	686
255/70R16	111S	SL	OWL	357567286	225766	6.5 - 8.0	7.5	10.2	30.1	2,403	12	695
265/70R16	112T	SL	OWL	357317286	221751	7.0 - 9.0	8	10.7	30.6	2,469	12	682
265/75R16	116T	SL	OWL	357292286	225768	7.0 - 9.0	7.5	10.5	31.7	2,756	12	660
235/70R17	109S	XL	BSL	357672279	228662	6.0 - 8.0	7	9.5	30	2,271	12	697
245/70R17	110S	SL	BSL	357675279	228660	6.5 - 8.0	7	9.8	30.6	2,337	12	684
255/65R17	110S	SL	OWL	357756286	228663	7.0 - 9.0	7.5	10.2	30.1	2,337	12	691
255/70R17	112S	SL	OWL	357758286	228664	6.5 - 8.5	7.5	10.3	31.1	2,469	12	672
265/65R17	112T	SL	OWL	357338286	228661	7.5 - 9.5	8	10.7	30.6	2,469	12	684
265/70R17	115T	SL	OWL	357747286	221714	7.0 - 9.0	8	10.7	31.7	2,679	12	660
265/60R18	110S	SL	OWL	357525286	228666	7.5 - 9.5	8	10.7	30.5	2,337	12	685
265/65R18	114S	SL	OWL	357644286	228667	7.5 - 9.5	8	10.7	31.5	2,601	12	663
275/65R18	116T	SL	OWL	357759286	228665	7.5 - 9.5	8	11	32.1	2,756	12	651
275/55R20	113S	SL	BSL	357636279	228657	7.5 - 9.5	8.5	11.2	31.9	2,535	12	655
275/60R20	115S	SL	BSL	357678279	228658	7.5 - 9.5	8	11	33	2,679	12	634
EDGE AT LT												
31X10.50R15LT	109R	C	OWL	357510286	221745	7.0 - 9.0	8.5	10.6	30.5	2,270	15	685
LT215/85R16	115R	E	BSL	357517279	221737	5.5 - 7.0	6	8.6	30.5	2,680	15	682
LT225/75R16	115R	E	BSL	357468279	221734	6.0 - 7.0	6	8.8	29.3	2,680	15	710
LT235/85R16	120R	E	BSL	357485279	221720	6.0 - 7.5	6.5	9.3	31.7	3,042	15	656
LT245/75R16	120S	E	BSL	357722279	221716	6.5 - 8.0	7	9.8	30.5	3,042	15	682
LT265/75R16	123R	E	OWL	357475286	221732	7.0 - 8.0	7.5	10.5	31.7	3,415	15	656
LT285/75R16	126R	E	OWL	357746286	228635	7.5 - 9.0	8	11.3	33.1	3,750	15	628
LT235/80R17	120R	E	BSL	357730279	221738	6.0 - 7.5	6.5	9.3	31.8	3,085	15	654
LT245/70R17	119S	E	BSL	357707279	221735	6.5 - 8.0	7	9.8	30.6	3,000	15	679
LT245/75R17	121S	E	BSL	357727279	221736	6.5 - 7.5	7	9.8	31.5	3,195	15	660
LT265/70R17	121S	E	BSL	357726279	221718	7.0 - 8.5	8	10.7	31.7	3,195	15	656
LT285/70R17	121R	E	OWL	357750286	228669	7.5 - 9.0	8.5	11.5	33	3,195	15	638
LT275/65R18	123S	E	OWL	357732286	221741	7.5 - 9.0	8	11	32.1	3,415	15	648
LT275/70R18	125R	E	OWL	357511286	221740	7.0 - 8.5	8	11	33.4	3,640	15	623
LT275/65R20	126S	E	OWL	357735286	221743	7.5 - 9.5	8	11	34.1	3,750	15	610



POPULAR FITMENTS

- Chevrolet Colorado
- Chevrolet Silverado
- Chevrolet Trailblazer
- Dodge Dakota
- Ford Escape
- Ford Explorer
- Ford F-150
- GMC Sierra
- Jeep Grand Cherokee
- Jeep Liberty
- Jeep Wrangler
- RAM 2500
- Toyota Sequoia
- Toyota Tacoma
- Toyota Tundra

KELLY TIRES™

For more complete information, go to Tire-HQ™ at www.tire-hq.com.

©2019 The Goodyear Tire & Rubber Company. All rights reserved.

PLUS-SIZING DISCLAIMER WARNING: Before you replace tires, always consult the vehicle owner's manual and follow the vehicle manufacturer's replacement tire recommendations. Vehicle handling may be significantly affected by a change in tire size or type. When selecting tires that are different from the Original Equipment size, see a professional installer in order to make certain that proper clearance, load-carrying capacity and inflation pressure are selected. Never exceed the maximum load capacity and inflation pressure listed on the sidewall of the tire. Always drive safely and obey all traffic laws. Avoid sudden, sharp turns or lane changes. Failure to follow this warning may result in loss of control of the vehicle, leading to an accident and serious injury or death.