

KELLY TIRES™



EDGE™ HT

A Hardworking, Quality Tire with All-Season Traction for Everyday Driving

- **Proven tread pattern** for confidence in all-season conditions
- **Broad tread grooves** evacuate water and slush for an enhanced grip
- **Reinforced center rib** enhances handling and promotes even wear
- **Sturdy shoulder blocks** stabilize the tread footprint to promote long treadwear

60000
MILE TREAD LIFE
LIMITED WARRANTY*

95,000 Kilometres
SL sizes

50000
MILE TREAD LIFE
LIMITED WARRANTY*

80,000 Kilometres
LT sizes



KELLY  TIRES™

30day
test

*See 30-Day Test Drive brochure for complete details.



EDGE™ HT AVAILABLE SIZES

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	TREAD DEPTH (IN 32 ^{nds})	REVS/MILE
245/75R16	111S	SL	OWL	357566313	234245	6.5 - 8.0	7	9.8	30.5	2,403	12	686
255/70R16	111S	SL	OWL	357567313	234246	6.5 - 8.5	7.5	10.2	30.1	2,403	12	695
265/70R16	112S	SL	OWL	357564313	234242	7.0 - 9.0	8	10.7	30.6	2,469	12	682
265/75R16	116T	SL	OWL	357292313	234243	7.0 - 9.0	7.5	10.5	31.7	2,756	12	660
245/70R17	110S	SL	OWL	357675313	234244	6.5 - 8.0	7	9.8	30.6	2,337	12	684
255/70R17	112T	SL	OWL	357007313	234258	6.5 - 8.5	7.5	10.2	31.1	2,469	12	672
265/65R17	112T	SL	BSL	357338297	235303	7.5 - 9.5	8	10.7	30.6	2,469	12	684
265/70R17	115S	SL	OWL	357001313	234241	7.0 - 9.0	8	10.7	31.7	2,679	12	660
265/60R18	110T	SL	BSL	357085297	235302	7.5 - 9.5	8	10.7	30.5	2,337	12	685
265/65R18	114T	SL	BSL	357003297	235304	7.5 - 9.5	8	10.7	31.5	2,601	12	663
275/65R18	116T	SL	OWL	357759313	234248	7.5 - 9.5	8	11	32.1	2,756	12	651
275/55R20	113H	SL	BSL	357005297	234257	7.5 - 9.5	8.5	11.2	31.9	2,535	12	655
275/60R20	115H	SL	BSL	357008297	234262	7.5 - 9.5	8	11	33	2,679	12	633
285/45R22	114H	XL	BSL	357002297	234255	9.5 - 10.5	9.5	11.2	32.1	2,601	12	651
EDGE HT LT												
LT245/75R16	120R	E	BSL	357469297	234249	6.5 - 8.0	7	9.8	30.5	3,042	15	683
LT265/75R16	123R	E	OWL	357475313	234251	7.0 - 8.0	7.5	10.5	31.7	3,415	15	657
LT235/80R17	120R	E	BSL	357730297	234259	6.0 - 7.5	6.5	9.3	31.8	3,085	15	654
LT245/75R17	121R	E	BSL	357958297	234252	6.5 - 7.5	7	9.8	31.5	3,195	15	660
LT265/70R17	121R	E	OWL	357502313	234250	7.0 - 8.5	8	10.7	31.7	3,195	15	657
LT275/65R18	123R	E	OWL	357965313	234260	7.5 - 9.0	8	11	32.1	3,415	15	648
LT275/70R18	125R	E	OWL	357511313	234253	7.0 - 8.5	8	11	33.2	3,640	15	627
LT275/65R20	126R	E	BSL	357985297	234263	7.5 - 9.5	8	11	34.1	3,750	15	610



POPULAR FITMENTS

- Chevrolet Colorado
- Chevrolet Silverado
- Chevrolet Tahoe
- Ford F-150
- Ford Ranger
- Dodge Durango
- GMC Canyon
- GMC Sierra
- Jeep Grand Cherokee
- Nissan Frontier
- Nissan Titan
- RAM 1500
- Toyota Sequoia
- Toyota Tacoma
- Toyota Tundra



For more complete information, go to Tire-HQ™ at www.tire-hq.com.

©2019 The Goodyear Tire & Rubber Company. All rights reserved.

PLUS-SIZING DISCLAIMER WARNING: Before you replace tires, always consult the vehicle owner's manual and follow the vehicle manufacturer's replacement tire recommendations. Vehicle handling may be significantly affected by a change in tire size or type. When selecting tires that are different from the Original Equipment size, see a professional installer in order to make certain that proper clearance, load-carrying capacity and inflation pressure are selected. Never exceed the maximum load capacity and inflation pressure listed on the sidewall of the tire. Always drive safely and obey all traffic laws. Avoid sudden, sharp turns or lane changes. Failure to follow this warning may result in loss of control of the vehicle, leading to an accident and serious injury or death.